


	<h3>Specifications HC-PSC1</h3> <p>Read Range: PROX3 - Up to 4 inches (102 mm), P640 - Up to 4 inches (102 mm), P400 - Up to 1 inch (25 mm), P-710 - Up to 14 inches (356 mm), P900 - Up to 20 inches (508 mm) Size: Nominal 3.4 x 2.2 x 0.06 inches (86 x 55 x 1.5 mm) Weight: 0.3 oz. (9 g) Operation: Passive (no battery) Frequency: 125 KHz excitation Humidity: 0-95% non-condensing Operating Temperature: -40°F to +149°F (-40° C to +65° C) Operating Environment: Indoor / Outdoor Material: ABS Color: Off-white Slot Punch: Vertical Marking: Site code, card number and format ID</p> <p>The PSC-1 is based upon proven passive digital radio frequency identification (RFID) technology. Physical size is a nominal 3.4 x 2.2 x 0.06 inches (86x55x1.5 mm). It includes beveled edges, is constructed of durable ABS plastic and is backed by a lifetime warranty. A vertical slot punch is standard. Color is off-white.</p>
	<h3>Specifications HC-PSK3</h3> <p>Read Range: PROX3 - Up to 2 inches (51 mm), P640 - Up to 1 inches (25 mm), P400 - Up to 1 inch (25 mm), P710 - Up to 6 inches (152 mm), P900 - Up to 10 inches (254mm) Size: Nominal 1.5 x 1.2 x 0.15 inches (36 x 29 x 3.8 mm) Weight: 0.16 oz. (4.5 g) Operation: Passive (no battery) Frequency: 125 KHz excitation Humidity: 0-95% non-condensing Operating Temperature: -40°F to +149°F (-40° C to +65° C) Operating Environment: Indoor / Outdoor Material: ABS Color: Light Gray Eyelet: Reinforced Brass Marking: Site code, card number and format ID</p> <p>The PSK-3 is manufactured of light gray ABS, includes a brass reinforcement ring and is based upon proven passive radio frequency identification technology (RFID). Physical size is a nominal 1.5 x 1.2 x 0.15 inches (36x29x3.8 mm), making it one of the absolute smallest proximity key ring tags available.</p>

	<p>Specifications HC-PSI4 (46 MIL)</p> <p>Read Range: PROX3 - Up to 3 inches (76 mm), P640 - Up to 3 inches (76 mm), P400 - Up to 1 inch (25 mm), P710 - Up to 10 inches (254 mm), P900 - Up to 12 inches (305 mm) Size: Nominal 3.38 x 2.12 x 0.046 inches (85.9 x 53.8 x 1.17 mm) Weight: 0.19 oz. (5.5 g) Operation: Passive (no battery) Frequency: 125 KHz excitation Humidity: 0-95% non-condensing Operating Temperature: -40°F to +149°F (-40° C to +65° C) Operating Environment: Indoor / Outdoor Material: PVC Color: Glossy White Slot Punch: Vertical and Horizontal Indicators Marking: Site code, card number and format ID</p> <p>Graphics Quality Prox Card ISO Compliant Thickness for Badging Graphics Quality Printing to Both Sides. Portrait or Landscape Punch Capability. No Diminished Read Range. Available with magnetic stripe (GRMAG)</p>
	<p>Specifications HC-PSM-2P (31 MIL)</p> <p>Read Range: PROX3 - Up to 3 inches (76 mm), P640 - Up to 3 inches (76 mm), P400 - Up to 1 inch (25 mm), P710 - Up to 10 inches (254 mm), P900 - Up to 12 inches (305 mm) Size: Nominal 3.38 x 2.12 x 0.031 inches (85.9 x 53.8 x 0.79 mm) Weight: 0.17 oz. (5.1 g) Operation: Passive (no battery) Frequency: 125 KHz excitation Humidity: 0-95% non-condensing Operating Temperature: -40°F to +149°F (-40° C to +65° C) Operating Environment: Indoor / Outdoor Material: PVC Color: Glossy White Slot Punch: Vertical and Horizontal Indicators Marking: Site code, card number and format ID</p> <p>Graphics Quality Prox Card ISO Compliant Thickness for Badging Graphics Quality Printing to Both Sides. Portrait or Landscape Punch Capability. No Diminished Read Range. Available with magnetic stripe (GRMAG)</p>