



Specifications HC-P453 Mullion / HC-P455 Single Gang

Read Range: PSC-1 - Up to 1.5 inch (38 mm), PSI-4 - Up to 1 inch (25 mm), PSK-3 - Up to 1 inch (25 mm)
Size: P453 - 5.25 x 2.0 x 1.0 inches (134 x 51 x 25 mm); P455 - 4.5 x 3.0 x 1.0 inches (114 x 76 x 25 mm)
Weight: P453 - 24 oz. (680 g); P455 - 38.4 oz. (1088 g)
Input Voltage: +5 to 16 VDC
Power Supply: Linear supply recommended, 5 - 14 VDC
Current Draw: 5 mA min, 45 mA typical, 80 mA peak
LED Indicator: Four-state standard (red, green, amber, off)
Audio Tone: Standard External Piezo Beeper
Frequency: 125 KHz excitation
Compatibility: Pyramid, Hartmann, AWID, HID
Operating Temperature: -40°F to +149°F (-40° C to +65° C)
Operating Environment: Indoor / Outdoor
Cable Distance: Up to 500 ft (152 m)
Color: Brushed Stainless Steel with Amber Fiber-Tex®
Construction: Solid stainless steel body, Fiber-Tex® (bullet resistant) face with fully-potted epoxy weather and tamper resistant proximity core.
Mounting: P453 - On metal door or window frame (mullion) or flat surface. May be mounted directly on metal; P455 - US sized wall switch box
IP Rating: IP67
Certifications: CSA, UL, FCC, CE, C-Tick, IC



Specifications HC-P403 Mullion / HC-P405 Single Gang

Read Range: PSC-1 - Up to 6 inches (152 mm), PSI-4 - Up to 4 inches (101 mm), PSK-3 - Up to 4 inches (101 mm)
Size: P403 - 5.25 x 2.0 x 1.0 inches (134 x 51 x 25 mm); P405 - 4.5 x 2.75 x 1.0 inches (114 x 70 x 25 mm)
Weight: P403 - 6.4 oz. (181.4 g); P405 - 8 oz. (227 g)
Input Voltage: +5 to 16 VDC
Power Supply: Linear supply recommended, 5 - 14 VDC
Current Draw: 5 mA min, 45 mA typical, 80 mA peak
LED Indicator: Four state standard (red, green, amber, off)
Audio Tone: Standard External Piezo Beeper
Frequency: 125 KHz excitation
Compatibility: Pyramid, Hartmann, AWID, HID
Operating Temperature: -40°F to +149°F (-40° C to +65° C)
Operating Environment: Indoor / Outdoor
Cable Distance: Up to 500 ft (152 m)
Color: Black
Construction: One-piece polycarbonate block with fully-potted epoxy weather and tamper resistant proximity core
Mounting: P403 - Single piece design mounts directly to metal door or window frame (mullion) or flat surface. P405 - Single piece design mounts directly to metal or plastic single-gang wall box or flat surface. Tamperproof screws included.
IP Rating: IP67
Certifications: CSA, UL, FCC, CE, C-Tick, IC