



### Specifications HC-P710

**Read Range:** PSC-1 - Up to 15 inches (381 mm), PSI-4 - Up to 10 inches (254 mm), PSK-3 - Up to 6 inches (152 mm)

**Size:** 8.5 x 6.0 x 1.0 inches (216 x 152 x 25 mm)

**Weight:** 22.4 oz. (635 g)

**Input Voltage:** +5 to 16 VDC (12V nominal)

**Power Supply:** Linear supply recommended, 12 VDC

**Current Draw:** 200 mA typical, 600mA peak

**LED Indicator:** Oversized Four-State Standard (Red, Green, Amber, and Off)

**Audio Tone:** Standard External Piezo Beeper

**Frequency:** 125 KHz excitation

**Compatibility:** Pyramid, Hartmann, AWID, HID

**Operating Temperature:** -40°F to +149°F (-40° C to +65° C)

**Operating Environment:** Indoor / Outdoor

**Cable Distance:** Up to 500 ft (152 m)

**Color:** Black

**Construction:** Single piece plastic with fully-potted epoxy weather and tamper resistant proximity core.

**Mounting:** US- size single gang wall box or non-metallic flat surfaces.

**IP Rating:** IP65

**Certifications:** CSA, UL, FCC, CE, C-Tick.

The single-piece, easy-to-install HC-P710 delivers non-contact read ranges up to 15 inches (381 mm), and operates from 5 to 16 VDC. Physical size is 8.5 x 6.0 x 1.0 inches (216x152x26 mm). Allowing for both indoor and outdoor operation, the electronics are secured in tamper-resistant epoxy potting.